

(19) World Intellectual Property
Organization
International Bureau



549724

(43) International Publication Date
30 September 2004 (30.09.2004)

PCT

(10) International Publication Number
WO 2004/082842 A1

(51) International Patent Classification⁷: **B03D 1/16**,
1/18, 1/20, 1/22

Gerard [AU/AU]; 22 Maud Road, Forrestfield, WA 6058
(AU).

(21) International Application Number:
PCT/AU2004/000316

(74) Agent: SHELSTON IP; 60 Margaret Street, Sydney NSW
2000 (AU).

(22) International Filing Date: 16 March 2004 (16.03.2004)

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003901208 17 March 2003 (17.03.2003) AU

(71) Applicant (*for all designated States except US*): OUT-
OKUMPU OYJ [FI/FI]; Riihitontuntie 7D, FIN-02200 Es-
poo (FI).


(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): BOURKE, Peter,

[Continued on next page]

(54) Title: A SEPARATE SIZE FLOTATION DEVICE



(57) Abstract: The invention provides a flotation device including a series of flotation tanks (1) for processing a slurry incorporating valuable minerals for extraction. At least one of the tanks includes a side outlet (15) adapted for the withdrawal of targeted relatively fine coarse particles from the slurry. The tanks also include a bottom outlet (14) for the withdrawal of relatively dense or coarse components of the slurry. The incorporation of bottom and side outlets allows the slurry to be separated into two parallel streams, one configured for optimal recovery of the relatively coarse or dense slurry components and the other for optimal recovery of the relatively fine slurry components. In this way, outflow slurry from downstream tanks in the coarse particle stream has a higher proportion of coarser particles than was present in the inflow slurry from the upstream tanks. Consequently, when a flotation reagent is added to the slurry in the downstream tanks, there is a greater probability of coating some of the larger particles. Therefore, the probability of floating these larger particles increases in the downstream tanks. This in turn increases the overall efficiency of the flotation process.



GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

— with international search report

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.